210105US

PATENT

APPLICATION FOR UNITED STATES LETTERS PATENT

for

A PROCESS TO PRODUCE A DILUTE ETHYLENE STREAM AN A DILUTE PROPYLENE STREAM

by

Rodney L. Porter, Anne M. Balinsky and Eric P. Weber

EXPRESS MAIL MAILING LABEL

NUMBER: **EL732382407US**
DATE OF DEPOSIT. **November 16, 2001**

I hereby certify that this paper is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 C F.R. 1.10 on the date indicated above and is addressed to: BOX PATENT APPLICATION, Commissioner for Patents. Washington, D C. 20231.

Vikki M. Meriwether

Vikki M. Meriwether

FIELD OF THE INVENTION

This invention is related to the field of processes wherein a cracked gas stream is separated to produce dilute olefin streams to be used as feedstocks to produce olefin-based derivatives. Specifically, this invention is related to the field of processes wherein a cracked gas stream is separated to produce a dilute ethylene stream and a dilute propylene stream to be used as feedstocks for producing olefin-based derivatives. More specifically, the dilute ethylene stream is used as a feedstock to produce ethylbenzene, and the dilute propylene stream is used as a feedstock to produce cumene, acrylic acid, propylene oxide or other propylene based derivatives.

BACKGROUND OF THE INVENTION

Feedstock costs in the chemical industry comprise a significant portion of the manufacturing costs. Continuous research is being conducted to lower these costs by utilizing lower cost feed sources. The alkylation of benzene and other aromatics is one area where dilute olefin streams are employed to reduce feed related manufacturing costs. For example, in the production of ethylbenzene, a raw material for the production of styrene, the off-gas from a fluidized catalytic cracking unit (FCC) can be successfully employed as a cost advantaged ethylene source. The FCC off-gas is a dilute stream containing typically less than 30 mole percent ethylene. Due to the large quantities of diluents in the FCC off-gas, such as, for example, hydrogen and methane, the alkylation section of the ethylbenzene unit requires that some of the equipment be oversized. Additionally, the hydrogen sulfide content of the FCC off-gas necessitates its removal in a gas pre-treatment section and subsequent compression before it can be routed to the alkylation reactor. The requirements of having oversized equipment and gas pre-treatment followed by compression greatly increase the capital costs associated with an ethylbenzene unit utilizing FCC off-gas as its feedstock compared to a conventional ethylbenzene unit that utilizes high purity, polymer grade ethylene.

There is a need in the chemical industry to reduce feedstock costs by utilizing dilute olefin streams at olefins-based derivative units rather than polymer grade olefin feedstocks. To fulfill this need, the inventors provide this inventive process. This process reduces the amount of equipment traditionally required for the production of ethylene. An example of some of the equipment that has been eliminated is the ethylene refrigeration compressor, demethanizer, cold box system, and C_2 and C_3 splitters. Additionally, some equipment is smaller than with conventional crackers of comparable scale. The propylene refrigeration system is reduced in size over that of a conventional cracker.

SUMMARY OF THE INVENTION

An object of this invention is to provide a process to produce a dilute ethylene stream and a dilute propylene stream from a cracked gas stream.

Another object of this invention is to provide a process to produce the dilute ethylene stream and the dilute propylene stream from a cracked gas stream generated by the steam cracking of C_2 and higher hydrocarbons.

Another object of this invention is to provide a process to produce the dilute ethylene stream and dilute propylene stream wherein these streams are utilized to produce olefin-based derivatives.

Another object of this invention is to provide a process to produce a dilute ethylene stream wherein the dilute ethylene stream is used as a feedstock to produce ethylbenzene.

Yet another object of this invention is to provide a process to produce a dilute propylene stream wherein the dilute propylene stream is used as a feedstock to produce cumene, acrylic acid, propylene oxide and other propylene derivatives.

In accordance with one embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream from a cracked gas stream is provided, the process

comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) separating the cracked gas stream in a deethanizer zone to produce a C_2 – stream and a C_3+ stream;

(2). hydrogenating the C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream;

(3) separating the C_3+ stream in a depropanizer zone to produce a C_3- stream and a C_4+ stream; and

(4) reacting the C_3- stream in a methylacetylene-propadiene hydrogenation (MAPD) reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream.

In accordance with another embodiment of this invention, a process for producing the cracked gas stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of"):

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the raw cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized, cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream; and

(5) drying the wet cracked gas stream in a drying zone to reduce the moisture level to form a cracked gas stream.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) separating the cracked gas stream in a deethanizer zone to produce a C_2 – stream and a C_3+ stream;

(2) compressing the C_2- stream in a compression zone to form a pressurized C_2- stream;

(3) hydrogenating the pressurized C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream;

(4) separating the C_3+ stream in a depropanizer zone to produce a C_3- stream and a C_4+ stream; and

(5) reacting the C_3- stream in a MAPD reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) hydrogenating a portion of the acetylene in the cracked gas stream in a hydrogenation zone to produce a reduced acetylene cracked gas stream;

(2) separating the reduced acetylene cracked gas stream in a deethanizer zone to produce the dilute ethylene stream and a C_3+ stream;

(3) separating the C_3+ stream in the depropanizer zone to produce a C_3- stream and a C_4+ stream; and

(4) reacting the C_3- stream in a MAPD reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream;

(5) drying the wet cracked gas stream in a drying zone to form a cracked gas stream;

(6) separating the cracked gas stream in a deethanizer zone to produce a C_2- stream and a C_3+ stream;

(7) compressing the C_2- stream in a second compression zone to form a pressurized C_2- stream;

(8) hydrogenating the pressurized C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream; and

(9) separating the C_3+ stream in a depropanizer zone to produce the dilute propylene stream and a C_4+ stream.

(10) reacting the C_3- stream in a MAPD reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons, and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized, cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream;

(5) drying the wet cracked gas stream in a drying zone to form a cracked gas stream;

(6) separating the cracked gas stream in a deethanizer zone to produce a C_2- stream and a C_3+ stream;

(7) hydrogenating the C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream; and

(8) separating the C_3+ stream in a depropanizer zone to produce the dilute propylene stream and a C_4+ stream.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the raw cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched. cracked gas stream in a first compression zone to form a pressurized, cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream; and

(5) drying the wet cracked gas stream in a drying zone to reduce the moisture level to form a cracked gas stream

(6) hydrogenating a portion of the acetylene in the cracked gas stream in a hydrogenation zone to produce a reduced acetylene cracked gas stream;

(7) separating the reduced acetylene cracked gas stream in a deethanizer zone to produce the dilute ethylene stream and a C_3+ stream;

(8) separating the C_3+ stream in the depropanizer zone to produce a C_3- stream and a C_4+ stream; and

(9) reacting the C_3- stream in a MAPD reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) separating the cracked gas stream in a deethanizer zone to produce a C_2 – stream and a C_3+ stream;

(2). hydrogenating the C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream;

(3) routing the C_3+ stream to storage or other process unit.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) separating the cracked gas stream in a deethanizer zone to produce a C_2 – stream and a C_3+ stream;

(2) compressing the C_2- stream in a compression zone to form a pressurized C_2- stream;

(3) hydrogenating the pressurized C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream;

(4) routing the C_3+ stream to storage or other process unit.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) hydrogenating a portion of the acetylene in the cracked gas stream in a hydrogenation zone to produce a reduced acetylene cracked gas stream;

(2) separating the reduced acetylene cracked gas stream in a deethanizer zone to produce the dilute ethylene stream and a C_3+ stream;

(3) routing the C_3+ stream to storage or other process unit.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream;

(5) drying the wet cracked gas stream in a drying zone to produce a cracked gas stream.

(6) separating the cracked gas stream in a deethanizer zone to produce a C_2- stream and a C_3+ stream;

(7) compressing the C_2- stream in a second compression zone to form a pressurized C_2- stream;

(8) hydrogenating the pressurized C_2- stream in a hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream; and

(9) routing the C_3+ stream to storage or other process unit.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of"):

(1) heating a hydrocarbon feed in a cracking zone to form a cracked gas stream; wherein the cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons, and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream;

(5) drying the wet cracked gas stream in a drying zone to produce a cracked gas stream;

(6) separating the cracked gas stream in a deethanizer zone to produce a C_2- stream and a C_3+ stream;

(7) hydrogenating the pressurized, C_2- stream in the hydrogenation zone to remove a portion of the acetylene to produce the dilute ethylene stream; and

(8) routing the C_3+ stream to storage or other process unit.

In accordance with another embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream is provided, the process comprising (or optionally, "consisting essentially of" or "consisting of") the following steps in the order named:

(1) heating a hydrocarbon feed in a cracking zone to form a raw cracked gas stream; wherein the raw cracked gas stream comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons, and heavier constituents;

(2) quenching the raw cracked gas stream in a quenching zone to produce a quenched, cracked gas stream;

(3) compressing the quenched, cracked gas stream in a first compression zone to form a pressurized cracked gas stream;

(4) deacidifying the pressurized, cracked gas stream in a deacidifying zone to remove a portion of the hydrogen sulfide to form a wet cracked gas stream; and

(5) drying the cracked gas stream in a drying zone to produce a cracked gas stream.

(6) hydrogenating a portion of the acetylene in the cracked gas stream in a hydrogenation zone to produce a reduced acetylene cracked gas stream;

(7) separating the reduced acetylene cracked gas stream in a deethanizer zone to produce the dilute ethylene stream and a C_3+ stream;

(8) separating the C_3+ stream in the depropanizer zone to produce a C_3- stream and a C_4+ stream; and

(9) reacting the C_3- stream in a MAPD reactor zone to convert a portion of methylacetylene and propadiene to propylene and propane to produce the dilute propylene stream.

These objects, and other objects, will become more apparent to others with ordinary skill in the art after reading this disclosure.

DETAILED DESCRIPTION OF THE INVENTION

In a first embodiment of this invention, a process for producing a dilute ethylene stream and a dilute propylene stream from a cracked gas stream is provided as shown in Figure 1.

Step (1) is separating the cracked gas stream in line **10** in a deethanizer zone **15** to produce a C_2- stream in line **20** and a C_3+ stream in line **45**. The deethanizer zone **15** comprises a fractionator sufficient to produce the C_2- stream in line **20** and a C_3+ stream in line **45**. The C_2- stream comprises hydrogen, methane, ethane, acetylene and ethylene. The C_3+ stream comprises C_3 hydrocarbons and heavier constituents. The cracked gas in line **10** comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons, and heavier constituents, and can be produced by any means known in the art.

Step (2) is hydrogenating the C_2- stream in line **20** in a hydrogenation zone **25** to remove a portion of the acetylene to produce the dilute ethylene stream in line **30.** Hydrogenation in the hydrogenating zone **25** can be completed by any means known in the art. For example, an

acetylene reactor containing catalyst can be utilized to hydrogenate a portion of the acetylene. Typically, Group VIII metal hydrogenation catalysts are utilized. Hydrogenation catalysts are disclosed in U.S. Patent Numbers 3,679,762; 4,571,442; 4,347,392; 4,128,595; 5,059,732; 5,488,024; 5,489,565; 5,520,550; 5,583,274; 5,698,752; 5,585,318; 5,587,348; 6,127,310 and 4,762, 956; all of which are herein incorporated by reference. Generally, the amount of acetylene remaining in the dilute ethylene stream in line **30** is in a range of less than about 5 ppm by weight, preferably, in a range of 0.5 ppm to 3 ppm by weight.

The temperature and pressure in the hydrogenation zone **25** is that which is sufficient to substantially hydrogenate the acetylene in the C_2- stream in line **20**. Preferably, the hydrogenating occurs at a temperature in a range of about 50°F to about 400°F and at a pressure in a range of about 350 psia to about 600 psia.

Generally, the amount of ethylene in the dilute ethylene stream in line **30** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene stream in line **30** then can be routed to an dilute ethylene derivative unit **35** to produce different chemicals in line **40** including, but not limited to, ethylbenzene. Preferably, the dilute ethylene stream in line **30** is routed to an ethylbenzene unit. The ethylbenzene unit can utilize any process known in the art. Typically, a Friedel-Crafts alkylation reaction of benzene by ethylene is used. Optionally, a effluent gas stream in line **41** from the dilute ethylene derivative unit **35** can be recycled to a cracking zone **105,** shown in Figure 2, to produce more dilute ethylene. The composition of the effluent gas stream can vary widely depending on the predominant hydrocarbon feed initially fed to the cracking zone. Typically, the effluent gas stream comprises hydrogen, methane, and other light hydrocarbons. Hydrogen and methane may need to be removed from the dilute process stream prior to recycle. This removal can be accomplished by separation membranes, separators, or other equipment.

Step (3) is separating the C_3+ stream in line **45** in a depropanizer zone **50** to produce a C_3- stream in line **55** and a C_4+ stream in line **80**. The depropanizer zone **50** comprises a fractionator sufficient to produce the C_3- stream in line **55** and a C_4+ stream in line **80**. The C_3- stream in line **55** comprises propane, propylene, methylacetylene and propadiene. The amount of propylene in the C_3- stream in line **55** is in a range of about 55% to about 98% by weight, preferably, in a range of 85% to 96% by weight. The C_4+ stream in line **80** comprises C_4 hydrocarbons and heavier hydrocarbon constituents.

Step (4) is reacting the C_3- stream in line **55** in a MAPD reactor zone **60** to remove a portion of methylacetylene and propadiene to produce the dilute propylene stream in line **62**. The hydrogenation process for the reduction of MAPD occurs in the MAPD reactor zone **60** can be completed by any means known in the art. Generally, the amount of methylacetylene and propadiene remaining in the dilute propylene stream in line **62** is less than 2 ppm by weight.

The dilute propylene stream in line **62** can be routed to an dilute propylene derivative unit **70** to produce different dilute propylene derivatives. For example, the dilute propylene stream in line **62** can be routed to a process to produce cumene, propylene oxide or acrylic acid in line **75**. Cumene can be produced by any process known in the art. Typically, a Friedel-Crafts alkylation reaction of benzene by propylene is used to produce cumene. Cumene then can be used to produce other products, such as, for example, phenols.

Optionally, the C_4+ stream in line **80** is separated in a debutanizer zone **85** to produce a C_4 stream in line **90** and a C_5+ stream in line **95**. The debutanizer zone **85** comprises a fractionator sufficient to produce the C_4 stream in line **90** and a C_5+ stream in line **95**. The C_4 stream in line **90** comprises C_4 hydrocarbons. The C_5+ stream in line **95** comprises C_5 hydrocarbons and heavier hydrocarbon constituents.

Optionally, the C_5+ stream in line **95** is treated in a hydrotreating zone **98** to produce a C_5 diolefins stream in line **96**, a benzene-toluene-xylenes (BTX) stream in line **99**, a

dicyclopentadiene (DCPD) stream in line **97** and a fuel oil stream in line **94**. The treatment of the C5+ stream in the hydrotreating zone **98** can be accomplished by any means known in the art. For example, U.S patent number 6,258,989 discloses a hydrotreating zone that can be utilized in this invention, herein incorporated by reference. The C_5 diolefins stream in line **96** comprises C_5 hydrocarbons, and the BTX stream in line **99** comprises benzene, toluene, and xylenes. The DCPD stream in line **97** comprises dicyclopentadiene, and the fuel oil stream in line **94** comprises C_8+ hydrocarbons.

In a second embodiment of the invention, the cracked gas stream utilized as the feedstock in this process can be produced by any process known in the art. A preferred process for producing the cracked gas stream is provided as shown in Figure 2.

Step (1) is heating a hydrocarbon feed in line **100** in a cracking zone **105** to produce a raw cracked gas stream in line **110**. Generally, the hydrocarbon feed in line **100** comprises at least one hydrocarbon selected from the group consisting of ethane, propane, butane, pentane, naphtha, gas condensates, gas oils, and mixtures thereof. Preferably, a majority of the hydrocarbon feed in line **100** consists of C_5 hydrocarbons and higher hydrocarbons.

The cracking zone **105** comprises at least one radiant furnace reactor capable of producing the raw cracked gas stream in line **110**. Typically, dilution stream is added to the radiant furnace reactors to reduce coking and to reduce the partial pressure of the hydrocarbon feed, thus increasing ethylene yield. Radiant furnace reactors are disclosed in U.S. Patent Numbers 5,151,158; 4,780,196; 4,499,055; 3,274,978; 3,407,789; and 3,820,955; all of which are herein incorporated by reference.

The raw cracked gas in line **110** comprises hydrogen, methane, C_2 hydrocarbons, C_3 hydrocarbons, and heavier constituents. Generally, the raw cracked gas stream in line **110** comprises at least about 10% by weight ethylene, preferably, at least about 20% by weight ethylene, and most preferably, at least about 30% by weight ethylene. For example, the raw

cracked gas stream in line **110** comprises about 1 to about 5 weight percent hydrogen, about 3 to about 25 weight percent methane, less than 1 weight percent acetylene, about 25 to about 35 weight percent ethylene, about 3 to about 45 weight percent ethane, and up to about 55 weight percent C_3+ hydrocarbons, depending on the hydrocarbon feed.

Step (2) is quenching the raw cracked gas stream in line **110** in a quenching zone **115** to produce a quenched, cracked gas stream in line **120**. Typically, the raw cracked gas stream in line **110** is quenched in quenching zone **115** to a temperature below which the cracking reaction substantially stops in order to prevent coking. Generally, the raw cracked gas stream in line **110** is cooled to a temperature below about 1100°F to substantially stop the cracking reaction. Preferably, the raw cracked gas stream in line **110** is cooled to a temperature in a range of about 650 to about 1100 °F. Quenching can be effected by any means known in the art. For example, the raw cracked gas stream in line **110** can be passed to a quench boiler and quench tower where fuel oil and dilution stream can be removed. Cooling of a raw cracked gas stream is disclosed in U.S. Patents 3,407,798; 5,427,655; 3,392,211; 4,3351,275; and 3,403,722, all herein incorporated by reference.

Step (3) is compressing the quenched, cracked gas stream in line **120** in a first compression zone **125** to produce a pressurized, cracked gas stream in line **130**. The pressure of the pressurized, cracked gas stream in line **130** is in a range of about 150 psig to about 650 psig. The first compression zone **125** comprises at least one gas compressor. Any gas compressor known in the art can be utilized.

Step (4) is deacidifying the pressurized, cracked gas stream in line **130** in a deacidifying zone **135** to remove a portion of the hydrogen sulfide and carbon dioxide to form a wet cracked gas stream in line **140**. Generally, the wet cracked gas stream in line **140** has a hydrogen sulfide concentration less than about 0.1 ppm by weight, preferably, in a range of 25 to 100 ppb by weight. Generally, the wet cracked gas stream has a carbon dioxide concentration of less than

about 5 ppm by weight. The hydrogen sulfide can be removed in the deacidifying zone **135** by any means known in the art. For example, diethanolamine or caustic contactors can be used to remove hydrogen sulfide and carbon dioxide.

Step (5) is drying the wet cracked gas stream in line **140** in a drying zone **145** to produce the cracked gas stream in line **150**. Generally, the water content of the cracked gas stream in line **150** is sufficiently dry to prevent downstream operational problems. Preferably, the water content of the cracked gas stream is in line **150** is less than 10 ppm by weight. Drying in drying zone **145** can be accomplished by any means known in the art. For example, molecular sieve beds can be utilized to remove water from the wet cracked gas stream in line **140**.

In a third embodiment of this invention, a process for producing a dilute ethylene stream and dilute propylene stream from a cracked gas stream is provided as shown in Figure 3.

Step (1) is separating the cracked gas stream in line **155** in a deethanizer zone **160** to produce a C_2- stream in line **165** and a C_3+ stream in line **200**. The deethanizer zone **160** comprises a fractionator sufficient to produce the C_2- stream in line **165** and a C_3+ stream in line **200**. The C_2- stream comprises hydrogen, methane, ethane, acetylene and ethylene. The C_3+ stream comprises C_3 hydrocarbons and heavier constituents.

Step (2) is compressing the C_2- stream in line **165** in a second compression zone **170** to produce a pressurized, C_2- stream in line **175**. The pressure of the pressurized, C_2- stream in line **175** is in a range of about 150 to about 650 psig, preferably, in a range of 200 to 650 psig. The second compression zone **170** comprises a gas compressor and related equipment. Any gas compressor known in the art can be utilized.

Step (3) is hydrogenating the pressurized C_2- stream in line **175** in a hydrogenation zone **180** to remove a portion of the acetylene to produce the dilute ethylene stream in line **185**. The hydrogenation zone **180** is the same as previously described in the first embodiment.

Generally, the amount of ethylene in the dilute ethylene stream in line **185** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene stream in line **185** then can be routed to an dilute ethylene derivative unit **190** to produce different chemicals in line **195** including, but not limited to, ethylbenzene. The dilute ethylene derivative unit **190** is the same as dilute ethylene derivative unit **35** previously described in the first embodiment. Optionally, an effluent gas stream in line **191** from the dilute ethylene derivative unit **190** can be recycled to a cracking zone **105** in Figure 2.

Step (4) is separating the C_3+ stream in line **200** in a depropanizer zone **205** to produce a C_3- stream in line **210** and a C_4+ stream in line **235**. The depropanizer zone **205** and the C_3- stream and the C_4+ stream are the same as previously described in the first embodiment.

Step (5) is reacting the C3- stream in line **210** in a MAPD reactor zone **215** to remove a portion of methylacetylene and propadiene to produce the dilute propylene stream in line **217**. The MAPD reactor zone **215** is the same as MAPD reactor zone **60** previously described in the first embodiment.

The dilute propylene stream in line **217** then can be routed to a dilute propylene derivative unit **225** to produce different dilute propylene derivatives. The dilute propylene derivative unit **225** is the same as dilute propylene derivative unit **70** previously described in the first embodiment.

Optionally, the C_4+ stream in line **235** is separated in a debutanizer zone **240** to produce a C_4 stream in line **245** and a C_5+ stream in line **250**. The debutanizer zone **240** comprises a fractionator sufficient to produce the C_4 stream in line **245** and a C_5+ stream in line **250**. The debutanizer zone **240** and the C_4 stream in line **245** and the C_5+ stream in line **250** are the same as previously described in the first embodiment.

Optionally, treating the C_5+ stream is treated in line **250** in a hydrotreating zone **255** to produce a C_5 diolefins stream in line **256,** a BTX stream in line **257,** the DCPD stream in line

258, and a fuel oil stream in line **254**. The hydrotreating zone **255,** the C_5 diolefins stream in line **256**, the BTX stream in line **257,** and the DCPD stream in line **258** and the fuel oil stream in line **254** are the same as previously described in the first embodiments.

In a fourth embodiment of this invention, a process for producing a dilute ethylene and dilute propylene stream from a cracked gas stream is provided as shown in Figure 4.

Step (1) is hydrogenating the cracked gas stream in line **260** in a hydrogenation zone **265** to remove a portion of the acetylene to produce a reduced acetylene cracked gas stream in line **270.** The hydrogenation zone **265** is the same as previously described in the first embodiment.

Step (2) is separating the reduced acetylene cracked gas stream in line **270** in a deethanizer zone **275** to produce the dilute ethylene stream in line **280** and a C_3+ stream in line **295**. The deethanizer zone **275** comprises a fractionator sufficient to produce the dilute ethylene stream in line **280** and a C_3+ stream in line **295**. The deethanizer zone **275**, dilute ethylene stream in line **280** and C_3+ stream in line **295** are the same as previously described in the first and third embodiments.

Generally, the amount of ethylene in the dilute ethylene stream in line **280** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene stream in line **280** then can be routed to an dilute ethylene derivative unit **285** to produce different chemicals in line **290** including, but not limited to, ethylbenzene. The dilute ethylene derivative unit **285** is the same as dilute ethylene derivative unit **35** previously described in the first embodiment. . Optionally, an effluent gas stream in line **286** from the dilute ethylene derivative unit **285** can be recycled to a cracking zone **105** in Figure 2.

Step (3) is separating the C_3+ stream in line **295** in a depropanizer zone **300** to produce a C_3- stream in line **305** and a C_4+ stream in line **330**. The depropanizer zone **300,** the C_3- stream in line **305,** and the C_4+ stream in line **330** are the same as previously described in the first and third embodiments.

Step (4) is reacting the C_3- stream in line **305** in a MAPD reactor zone to remove a portion of methylacetylene and propadiene to produce the dilute propylene stream in line **312**. The MAPD reactor zone **310** is the same as previously described in the first and third embodiments.

The dilute propylene stream in line **312** can be routed to a dilute propylene derivative unit **320** to produce different dilute propylene derivatives. The dilute propylene derivative unit **320** is the same as previously described in the first and third embodiments.

Optionally, the C_4+ stream in line **330** is separated in a debutanizer zone **335** to produce a C_4 stream in line **340** and a C_5+ stream in line **345**. The debutanizer zone **335** comprises a fractionator sufficient to produce the C_4 stream in line **340** and a C_5+ stream in line **345**. The debutanizer zone **335**, the C_4 stream in line **340**, and the C_5+ stream in line **345** are the same as previously described in the first and third embodiments.

Optionally, the C_5+ stream is treated in line **345** in a hydrotreating zone **350** to produce a C_5 diolefins stream in line **35**, a BTX stream in line **352**, a DCPD stream in line **353**, and a fuel oil stream in line **354**. The hydrotreating zone **350**, the C_5 diolefins stream in line **351**, the BTX stream in line **352**, the DCPD stream in line **353**, and the fuel oil stream in line **354** are the same as previously described in the first and third embodiments.

In a fifth embodiment of this invention, a process for producing a dilute ethylene stream from a cracked gas stream is provided as shown in Figure 5.

Step (1) is separating the cracked gas stream in line **300** in a deethanizer zone **305** to produce a C_2- stream in line **315** and a C_3+ stream in line **310**. The deethanizer zone **300** comprises a fractionator sufficient to produce the C_2- stream in line **315** and a C_3+ stream in line **310**. The C_2- stream comprises hydrogen, methane, ethane, acetylene and ethylene. The C_3+ stream comprises C_3 hydrocarbons and heavier constituents.

Step (2) is hydrogenating the C_2- stream in line **315** in a hydrogenation zone **320** to remove a portion of the acetylene to produce the dilute ethylene stream in line **325.** The hydrogenation zone **320** is the same as previously described in the first embodiment.

Generally, the amount of ethylene in the dilute ethylene stream in line **325** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene stream in line **325** then can be routed to an dilute ethylene derivative unit **330** to produce different chemicals in line **335** including, but not limited to, ethylbenzene. The dilute ethylene derivative unit **330** is the same as dilute ethylene derivative unit **35** previously described in the first embodiment . Optionally, an effluent gas stream in line **331** from the dilute ethylene derivative unit **330** can be recycled to a cracking zone **105** in Figure 2.

Step (3) is routing the C_3+ stream in line **310** to storage or to other process units.

In a sixth embodiment of this invention, a process for producing a dilute ethylene stream from a cracked gas stream is provided as shown in Figure 6.

Step (1) is separating the cracked gas stream in line **400** in a deethanizer zone **405** to produce a C_2- stream in line **415** and a C_3+ stream in line **410**. The deethanizer zone **405** comprises a fractionator sufficient to produce the C_2- stream in line **415** and a C_3+ stream in line **410**. The C_2- stream comprises hydrogen, methane, ethane, acetylene and ethylene. The C_3+ stream comprises C_3 hydrocarbons and heavier constituents.

Step (2) is compressing the C_2- stream in line **415** in a second compression zone **420** to produce a pressurized, C_2- stream in line **425**. The pressure of the pressurized, C_2- stream in line **425** is in a range of about 150 to about 650 psig , preferably, in a range of 200 to 650 psig. The second compression zone **420** comprises a gas compressor and related equipment. Any gas compressor known in the art can be utilized.

Step (3) is hydrogenating the pressurized C_2- stream in line **425** in a hydrogenation zone **430** to remove a portion of the acetylene to produce the dilute ethylene stream in line **435.** The hydrogenation zone **430** is the same as previously described in the first embodiment.

Generally, the amount of ethylene in the dilute ethylene stream in line **435** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene stream in line **435** then can be routed to an dilute ethylene derivative unit **440** to produce different chemicals in line **445** including, but not limited to, ethylbenzene. The dilute ethylene derivative unit **440** is the same as dilute ethylene derivative unit **35** previously described in the first embodiment. . Optionally, an effluent gas stream in line **441** from the dilute ethylene derivative unit **440** can be recycled to a cracking zone **105** in Figure 2.

Step (4) is routing the C_3+ stream in line **410** to storage or to other process units.

In a seventh embodiment of this invention, a process for producing a dilute ethylene from a cracked gas stream is provided as shown in Figure 7.

Step (1) is hydrogenating the cracked gas stream in line **500** in a hydrogenation zone **505** to remove a portion of the acetylene to produce a reduced acetylene cracked gas stream in line **510.** The hydrogenation zone **505** is the same as previously described in the first and third embodiment.

Step (2) is separating the reduced acetylene cracked gas stream in line **510** in a deethanizer zone **515** to produce the dilute ethylene stream in line **525** and a C_3+ stream in line **520**. The deethanizer zone **515** comprises a fractionator sufficient to produce the dilute ethylene stream in line **525** and a C_3+ stream in line **520.** The deethanizer zone **515**, dilute ethylene stream in line **525** and C3+ stream in line **520** are the same as previously described in the first and third embodiments.

Generally, the amount of ethylene in the dilute ethylene stream in line **525** is in a range of about 30% to about 60% by weight, preferably, 40% to 60 % by weight. The dilute ethylene

stream in line **525** then can be routed to an dilute ethylene derivative unit **530** to produce different chemicals in line **535** including, but not limited to, ethylbenzene. The dilute ethylene derivative unit **530** is the same as dilute ethylene derivative unit **35** previously described in the first embodiment.

Step (3) is routing the C_3+ stream in line **410** to storage or to other process units.

In another aspect of this invention, the second embodiment which provides a preferred process of producing the cracked gas stream, can be combined with either the first, third, fourth, fifth, sixth or seventh embodiments to yield one continuous process for producing the dilute ethylene stream and dilute propylene stream.